



## The thermal performance for cooling

### Proven design – highest process flexibility – low maintenance

For many processes the robust rotary/drum cooler is the optimum solution for cooling – either **for direct cooling of the material with air** or indirect cooling with water. High throughput rates, easy handling, great flexibility for coping with fluctuating material properties and quantities, high availability and low maintenance requirements are benefits of rotary coolers.

The Rotary Cooler always operates with direct contact of the bulk material and the cooling media in counter-current design.

Depending on the material characteristics, different shapes of blades/internals such as a scoop lifter can be selected for higher heat transfer between hot gas and material. The cooling air passes through the cooler counter-current to the material, thus providing the most efficient heat transfer and lowest product temperature. The flights inside the cooler are specially designed for improved cooling considering the particle sizes and heat transfer characteristics of the bulk material enabling for very large contact area with the cooling air. Optionally,

direct cooling can be enhanced by means of a water spray lance at the feed or at the discharge end respectively by external water spray on the cylinder of the drum.

If the feed temperature of the material to be cooled is very high, the feed end of the cooler can be fabricated from high temperature resistant steel or be refractory lined to ensure low maintenance.

The hot air leaving the cooler can be utilized as pre-heated secondary combustion air, increasing the overall efficiency of the thermal process.

# Rotary Cooler



## Fields of application

- Cooling of various free-flowing bulk materials such as
- Minerals and ores (iron ore, manganese ore, mineral sands, lime, dolomite, magnesite, etc.)
  - Proppants
  - Waelz furnace slag
  - Fertilizer (DAP, MAP, NPK, TSP, etc.)

## Main features

Counter-current design of material- and gas-flow to optimize cooling efficiency

Direct cooling of bulk material only with air or enhanced by water injection

Custom design and layout to maximize thermal efficiency

## Design parameters

Custom flight design for optimized cooling process

Variable speed drive system

Utilization of preheated air for enhanced thermal efficiency

Long or short residence time

Diameter: up to 6 m

Length: up to 60 m

## Contact

thyssenkrupp Industrial Solutions AG

Graf-Galen-Straße 17  
59269 Beckum, Germany  
Phone: +49 2525 99-0

E-mail: [pyro.tkis@thyssenkrupp.com](mailto:pyro.tkis@thyssenkrupp.com)

[www.thyssenkrupp-industrial-solutions.com/pyroprocessing](http://www.thyssenkrupp-industrial-solutions.com/pyroprocessing)

Sales Agent

© 2016 Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustration purposes only. The operation values are considered to be approximate and will be finally determined on the basis of the specific task and the material characteristics. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and thyssenkrupp makes no other warranty of accuracy, reliability, completeness, merchantability or fitness for any purpose, express or implied. Products and services listed may be trademarks, service marks or trade-names of thyssenkrupp and/or its subsidiaries in Germany and other countries. All rights are reserved.